

Janet Mae Purse Supply List

$\frac{3}{4}$ yard for outer main
 $\frac{3}{4}$ yard for lining, extra if you plan to make your pockets match your lining.
 $\frac{3}{4}$ yard for accent pieces
 $\frac{1}{2}$ - 1 yard for bias binding
 $\frac{1}{3}$ yard for strap if you are making your strap out of cotton and not using premade webbing/strapping, 2 yards if using premade webbing/strapping
1 yard SF101
1 $\frac{1}{3}$ yard of Foam (double sided fusible is recommended)
18" of size 5 "zippers by the yard" with 2 pulls
1 hardware set which includes: (available at RSC)
(2) 1 $\frac{1}{2}$ " triangle rings or d rings, (2) 1 $\frac{1}{2}$ " swivel hooks, and (1) 1 $\frac{1}{2}$ " strap adjuster)

You must come to class with your fabrics already quilted.

Create a quilt sandwich by layering the lining fabric right side down, foam in the middle, and exterior fabric right side up on the top. Iron and pin in place. Quilt as desired. A walking foot and longer stitch length helps this process whichever option you quilt with. There are 2 main ways to quilt your pieces:

The first is to follow the pattern instructions and quilt one large piece, then subcut into the smaller final pieces. If you do this, be sure you follow the instructions. **There are pieces that need cut BEFORE you quilt your large piece.**

**** Preferred method---**The second way is to cut all of your individual pieces out at least 1" LARGER each way than the final dimensions, then quilt each piece individually. If you choose the second way, **make sure you leave room for shrinkage** when quilting by allowing at least that extra inch. You will need $\frac{1}{3}$ yard more fusible foam if quilting separately.

The pattern calls for 2 yards of handle webbing-strapping. If you are not using a premade strap, you will need an additional yard of SF101 to interface your handle pieces.

The pattern does NOT call for bias binding around the curved edges. I have found that it needs bias binding or the corners will pucker and pleat. I used 1 yard to make my bias binding so I had long enough strips without piecing them, then cut the other pieces, except the pockets and strap, out of the pieces leftover.

notions needed:

Sewing machine with power cord and foot control

Standard machine foot

Zipper foot

Double sided tape ($\frac{1}{4}$ " wide)

Rotary cutter

Ruler

Fabric pen like frixion

Point turner

Thread to coordinate with your fabrics

Seam gauge

Seam ripper

Sharp scissors

Stiletto

Walking foot

$\frac{1}{4}$ " foot

